

TBUS-1Axl

Table Mount Modular Multi-Connection Solution - Tilt-Up Lid



The TBUS-1Axl is the enclosure of a new modular system with a tilt-up lid. A complete TBUS system requires the enclosure, an inner frame, a power socket, inserts and a power cord.

NOTE: The TBUS enclosure, power socket, power cord & inserts are purchased separately.

Photos Above Show A Fully Populated TBUS-1AxI

FEATURES

- Cover Manually opens & closes.
- Inner Frame 6 different "TIAF" inner frame options are available that can accommodate a combination of up to 4 power sockets, 6 cable pass-through or connector inserts, 1 long insert and up to 3 Kramer TOOLS.
- Power Sockets 8 different "TS" single and 8 dual power socket options are available to accommodate the power requirements worldwide.
- Power Cord 8 different "C-AC" single power cords (and 3 "Y" power cords) for each power socket.
- Optional Accessories TBUS Brackets, K-Able Box Cable Reels, Step-In Modules and Controllers are available.
- UL and CE Qualified.
- Connector Depth Adjustable.
- Installation Requirement Table cutout of 19.1cm x 15.2cm (7.51in x 5.98in).
- Dimensions 20.5cm x 17cm x 13.2cm (8.1" x 6.7" x 5.2") W, D, H.
- Weight TBUS-1AxI: 1.5kg (3.3lbs) approx.; table clamps: 0.26kg (0.57lbs); metal template: 0.125kg (0.28lbs).