


### 3Gbit Fiber Optic / SDI Transceiver

- SDI Fiber receiver and transmitter in single package
- Supports SDI video up to 3Gbit/s (1080p60)
- 3Gbit Level A and Level B support (all formats)
- Auto reclocking 270Mbit / 1.5Gbit / 2.97Gbit
- Error free optical connections
- Singlemode and Multimode versions
- Up to 10km (6.2 miles) @ 3Gbit/s (singlemode)
- Up to 300m (984 feet) @ 3Gbit/s (multimode)
- Duplex LC optical connection
- Supports hot swapping and hot plugging



Singlemode SFP      Multimode SFP

Using the same basic module we provide two versions suitable for singlemode or multimode fiber. Each version has a different SFP installed.


The OTR 1810 is a Fiber / SDI transmitter and receiver combined in a single self contained package. It is a convenient and cost effective solution to combat the restrictions involved with the distribution of uncompressed broadcast quality video signals over long distances.

Each OTR 1810 transceiver has an independent transmitter and receiver channel, which provides an effective solution for any SDI signal up to 1080p60 (3Gbit/s) while preserving full uncompressed quality.


The OTR 1810 will auto-detect and re-clock any 270Mbit / 1.5Gbit and 3Gbit SDI source prior to conversion. The module is fully compatible with 3Gbit Level A and Level B formats.

### Fiber Adapter Options

These adapter kits allow the use of ST or SC fiber connections on the module. SMF 0.5m (19.6") tail introduces less than 0.25dB attenuation.



Model# **LC/SC DUP**  
LC/PC to SC/PC Adapter



Model# **LC/ST DUP**  
LC/PC to ST/SC Adapter



### Technical Specifications

<b>SDI Video</b>	1 x SDI video input 1 x SDI Video output 75 Ohm BNC connectors
	SMPTE 424M, SMPTE 292M, SMPTE 259M, DVB-ASI
	Multi-standard operation from 270Mbit/s to 3Gbit/s
	Multi-rate reclocking 270Mbit/s - 1.48Gbit/s - 3Gbit/s
	Return Loss: > 15dB to 1.5GHz and > 10dB up to 3GHz
	Automatic cable EQ (Belden 1694A cable) 250m @ 270Mbit/s, 140m @ 1.5Gbit/s, 80m @ 3Gbit/s
<b>Fiber Optic</b>	1 x fiber optic input 1 x fiber optic output Duplex using LC Connections
	SMPTE 297M - 2006
	<b>Singlemode Version: OTR 1810</b> Transmitter: 1310nm (-5dBm) Receiver: 1260nm to 1620nm (-3dBm to -19dBm) Max. distance 10km (6.2 miles) @ 3Gbit/s
	<b>Multimode Version: OTR 1810 MM</b> Transmitter: 850nm (-5dBm) Receiver: 750nm to 880nm (0dBm to -15dBm) Max. distance 300m (984 feet) @ 3Gbit/s
	TX active LED, and RX active on side of module
<b>Power</b>	+12VDC @ 2.6W nominal - ( supports 7 - 16VDC input range )
<b>Physical</b>	Size: 140mm x 42mm x 22mm (5.51" x 1.65" x 0.86") including connectors Weight: 125g (4.4oz)
<b>Ambient</b>	5 - 40°C (41 - 104°F) 90% Humidity (non condensing)
<b>Model #</b>	OTR 1810 (Singlemode) - ( EAN# 4250479318144 ) OTR 1810 MM (Multimode) - ( EAN# 4250479359840 )
<b>Includes</b>	Module, AC power supply, transport case

### Power Adapter Options

The kit **INCLUDES** AC power supply. The power adapters below are optional.



**P-TAP 1000**  
Use with a standard battery P-TAP power source.



**XLR 1000**  
Use with a standard 4 pin XLR camera battery power source.

Specifications subject to change