



1642VLZ4

The 16-channel 1642VLZ4 delivers the proven performance of Onyx preamps in a compact 4-bus mixer design, perfect for bands, clubs and more.

From every input to every output, the 1642VLZ4 is designed to provide the highest headroom and lowest noise possible for maximum signal integrity.

Plus, it is truly “Built-Like-A-Tank” with a ridiculously rugged solid-steel chassis that includes high-contrast controls for ultimate tactile control.

And with features like an expanded return section for no-hassle system integration, plus a dedicated control room section, the 1642VLZ4 is the go-to mixer choice for any application that demands flexibility and professional performance.

APPLICATIONS:

Live sound mixing, houses of worship, clubs, gymnasiums, banquet halls, conference rooms, boardrooms, multitrack studio and field recording, video post-production, multimedia applications, broadcast and many, many more.



Like us



Follow us



Watch our dang videos

FEATURES:

- 16-channel mixer featuring our signature high-headroom, low-noise design
- 10 boutique-quality Onyx mic preamps
 - Ultra-wide 60 dB gain range
 - 128.5 dB dynamic range
 - +22 dBu line input handling
 - Extended frequency response
 - Distortion under 0.0007% [20 Hz – 50 kHz]
- Improved RF rejection, perfect for broadcast applications
- Phantom power for condenser mics
- 16 high-headroom line inputs with +4/–10 operation control
- 3-band EQ (80 Hz, 2.5 kHz, 12 kHz)
- 18 dB/oct 75 Hz low-cut filter on mic input channels
- Four aux sends, level, pan and PFL solo on each channel
- Four stereo returns for connecting FX processor or other stereo source
- 60 mm long-wearing log-taper faders
- ALT 3/4 stereo bus for added routing flexibility
- Control room / phones source matrix
- High-resolution 12-segment stereo meters
- Sealed rotary controls resist dust and grime
- “Built-Like-A-Tank” rugged steel chassis with powder-coat finish
- High-visibility, high-contrast controls deliver convenient “at-a-glance” visual feedback
- Rack-mountable design using optional rack ear kit
- Multi-voltage power supply for worldwide use

1642VLZ4 SPECIFICATIONS

Main Mix Noise

(20 Hz–20 kHz bandwidth, 1/4" main out, channel gains @ unity, channel EQs flat, all channels assigned to main mix, odd channels panned left, even channels panned right.)

Main mix fader unity, channel faders down: -86.5 dBu

(90 dB Signal to Noise Ratio, ref +4 dBu)

Main mix fader @ unity, channel faders @ unity: -86 dBu

Total Harmonic Distortion (THD)

(1 kHz @ 35 dB gain, 20 Hz–20 kHz bandwidth)

Mic in to insert send <0.0007%

Attenuation / Crosstalk

(1 kHz relative to 0 dBu, 20 Hz–20 kHz bandwidth, line in, 1/4" main out, gain @ unity)

Channel mute switch engaged -82 dBu

Channel gain knob down -82 dBu

Frequency Response

Mic input to main output (gain @ unity)

+0, -1 dB, 20 Hz to 50 kHz

+0, -3 dB, <10 Hz to >100 kHz

Equivalent Input Noise (EIN)

(Mic input to insert send out, max gain)

150 Ω termination -128.5 dBu
20 Hz–20 kHz

Common Mode Rejection Ratio (CMRR)

1 kHz better than -70 dB

Maximum Levels

Mic in +22 dBu

All other inputs +22 dBu

Main mix TRS out and XLR out +28 dBu

All other outputs +22 dBu

Impedances

Mic in 2.5 kΩ

Channel insert return 2.5 kΩ

All other inputs 10 kΩ or greater

Tape out 1.1 kΩ

All other outputs 120 Ω

3-Band EQ (Channels 1-8)

High Shelving ±15 dB @ 12 kHz

Mid Peaking ±15 dB sweep 100 Hz – 8 kHz

Low Shelving ±15 dB @ 80 Hz

Low Cut Filter 18 dB/octave, -3 dB @ 75 Hz

4-Band EQ (Channels 9-16)

High Shelving ±15 dB @ 12 kHz

Hi Mid Peaking ±15 dB @ 2.5 kHz

Low Mid Peaking ±15 dB @ 400 Hz

Low Shelving ±15 dB @ 80 Hz

Low Cut Filter 18 dB/octave, -3 dB @ 75 Hz

AC Power Requirements

Power Consumption 50 watts

US, JP 100 – 120 VAC, 50 – 60 Hz

EU, UK, AU, CN 200 – 240 VAC, 50 – 60 Hz

Operating Temperature 0° – 40°C

32° – 104°F

Fuse Rating

100-120V 1A slo blo, 5 x 20 mm

220-240V 0.5A slo blo, 5 x 20 mm

Physical Properties (product)

Height 16.7 in / 425 mm

Depth 5.2 in / 131 mm

Width 16.6 in / 421 mm

Weight 18.2 lb / 8.3 kg

Physical Properties (packaged product)

Height 9.4 in / 239 mm

Depth 19.9 in / 505 mm

Width 21.3 in / 541 mm

Weight 21.0 lb / 9.5 kg

Ordering Information

1642VLZ4 16-Channel Compact 4-Bus Mixer, US P/N 2040766-00




1642VLZ4 16-Channel Compact 4-Bus Mixer, EU P/N 2040766-01

1642VLZ4 16-Channel Compact 4-Bus Mixer, AU P/N 2040766-04

1642VLZ4 16-Channel Compact 4-Bus Mixer, CN P/N 2040766-05

1642VLZ4 16-Channel Compact 4-Bus Mixer, BZ P/N 2040766-06


1642VLZ4 DIMENSIONS



NOTES:

1. WEIGHT APPROX. 18.2 lb [8.3 kg]
2. SHIPPING WEIGHT APPROX. 21.0 lb [9.5 kg]

THIRD ANGLE PROJECTION



THE INFORMATION CONTAINED
HEREIN IS PROPRIETARY AND
CONFIDENTIAL PROPERTY OF
LOUD TECHNOLOGIES, INC.
ALL RIGHTS RESERVED

UNLESS OTHERWISE SPECIFIED:
ALL DIMENSIONS ARE IN INCHES
DUAL [MM] DIMENSIONS
FOR REF ONLY


TOLERANCE IN INCHES
LINEAR ± 0.13 in / ± 3.3 mm
ANGLES $\pm 1^\circ$

(X.XX) = REF DIMS
NO TOLERANCE IMPLIED

TSC = THEORETICAL SHARP CORNER

DIMENSIONS ACROSS CENTERLINES
TO BE SYMMETRICAL

1642VLZ4 BLOCK DIAGRAM






1642VLZ4

16-Channel 4-Bus Compact Mixer

1642VLZ4 FRONT AND REAR PANEL



LOUD Technologies Inc. is always striving to improve our products by incorporating new and improved materials, components, and manufacturing methods. Therefore, we reserve the right to change these specifications at any time without notice.

“Mackie” and the “Running Man” figure are registered trademarks of LOUD Technologies Inc. All other brands mentioned are trademarks or registered trademarks of their respective holders, and are hereby acknowledged.

©2013 LOUD Technologies Inc. All rights reserved.

Electronic files for this product are available at:
www.mackie.com

Specification Sheet

1642VLZ4_SS.PDF

Owner's Manual

1642VLZ4_OM.PDF



www.mackie.com
 16220 Wood-Red Road NE
 Woodinville, WA 98072 USA
 800-898-3211, Fax 425-487-4337

Part No. SW0995 Rev. A 08/13