

NEXUS™ UL® Contractor Series 5.25" or 6.5" 70V Commercial Metal Back Can Speakers

SP5NXCTUL 5.25" speaker
SP6NXCTUL 6.5" speaker

Features

- Heavy-duty, industrial metal back cans that provide component protection and safety while enhancing the speakers' full-range bass sound
- Removable "Quick-Snap" connection terminals provide easy access and optimal angles for connecting speaker wire
- A wattage selector dial simplifies transformer settings
- Mounted security loops allow for a support cable run and drop ceiling support brackets are included
- The 5.25" model has met the strict UL1480 requirements, while the 6.5" model has met both UL1480 and UL2043



sold in pairs

Specifications

	SP5NXCTUL	SP6NXCTUL
Woofer	5.25" Polypropylene woofer with rubber surround	6.5" Polypropylene woofer with rubber surround
Tweeter.....	3/4" Silk dome tweeter	3/4" Silk dome tweeter
Magnet.....	12 oz. Ferrite	12 oz. Ferrite
Frequency Response	75Hz – 20kHz	60Hz – 20kHz
Sensitivity	88dB (1W/1M)	87dB (1W/1M)
Impedance.....	8 Ohms	8 Ohms
Max. Power.....	80W	120W
Transformer	70V transformer switch	70V transformer switch
Transformer Settings	10W, 5W, 2.5W, 1.25W, 0.625W, 8 Ohms	30W, 15W, 7.5W, 3.7W, 1.9W, 8 Ohms
Terminator Type.....	Phoenix connection	Phoenix connection
Dimensions.....	9.25" (Dia.) x 7.25" (D)	10.25" (Dia.) x 7.75" (D)
Cut-Out Dimensions	7.8" (Dia.)	8.75" (Dia.)
UL Ratings.....	UL1480	UL1480, UL2043

Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 10/3/12

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com