

EasyUSB™ Solutions

Vaddio™ EasyTalk™ Sound Bar

High Quality Audio Solution for UC Conferencing Applications

Part Number: 999-8565-000 (Worldwide)

The EasyUSB EasyTalk Sound Bar is a 37" (940mm) wide speaker bar for use in UC conferencing rooms where the built-in flat panel HD monitor speakers just aren't good enough. This Sound Bar is ideal for placement above or below any HDTV or monitor.




Image: EasyTalk Sound Bar shown with the included Rubber Speaker feet

The EasyUSB EasyTalk Sound Bar is optimized for voice and provides clean, crisp audio while not over-emphasizing low bass or those barky midrange frequencies. The Sound Bar combines left, center and right channel speakers into a single, convenient wall or table top mountable enclosure. Each speaker channel uses a long excursion, foam surround 3.75" (92.3mm) paper cone woofer for superb dynamic impact and 5/8" (15.9mm) aluminum tweeter to ensure realistic high frequencies unlike the thin-sounding speakers built into HDTVs.

The sensitivity and frequency response of the Sound Bar is rated at 87 dB 1W/1m with a frequency response of 100 Hz to 20k Hz. Each speaker channel is rated at 8 ohms and can handle up to 80 watts per channel. The high-gloss black lacquer finish adds style to any décor and is extremely easy to install. It is packaged with a pair of rubber speaker feet for table-top or credenza mounting and keyhole slots and M5 threaded inserts provide for simple wall mount options.

EASYTALK SOUND BAR IMAGES

Front View: Speaker grill removed to expose three 3.75" high excursion woofers and three 5/8" aluminum tweeters in left, center and right speaker channel configuration.



Rear View: Showing three individual speaker binding posts (left/center/right) for each speaker channel. Keyhole slots and M5 threaded inserts allow for mounting flexibility.



GENERAL SPECIFICATIONS

Part Number	999-8565-000 (Worldwide)
Included Accessories	Packed with two (2) Rubber Speaker Feet and two (2) 6' (1.83m) lengths of 18/2 speaker wire (stripped and tinned)
Mounting Points	Two (2) Keyhole Slot Brackets and/or two (2) M5 Threaded Inserts
Speaker Channels	Three individual speaker channels (Left/Center/Right)
Speaker Impedance	8 Ohms per channel
Power Rating	Up to 80 watts per channel
Freq. Response	100 Hz to 20k Hz
Sensitivity	SPL: 87 dB 1W/1m
Speaker Elements (Optimized for Voice)	Three (3) 3.75" (92.3mm), long excursion, foam surround paper cone woofers, one per speaker channel, Three (3) 5/8" (15.9mm) aluminum tweeters, one per speaker channel
Finish	High-gloss black lacquer
Dimensions	4.75" (120.7mm) H x 37" (940mm) W x 4.25" (108mm) D
Weight	15 lbs. (6.804 kg) (approx.. 2700 Peanut M&Ms)

Learn more about our cameras, audio devices and controllers at 800-572-2011 or vaddio.com

vaddio

©2015 Vaddio - All Rights Reserved. Reproduction in whole or part without written permission is prohibited. Specifications and pricing are subject to change without prior notice or obligation. Vaddio, EasyUSB and EasyTalk are trademarks of Vaddio. All other trademarks are the property of their respective owners. Document 021115-2, SD: 68580.2

