

PRODUCT SPECIFICATIONS

(BCP-LD25HD)

CANARE ELECTRIC CO., LTD

1. Scope This product specification covers the performance of CANARE crimp type 75Ω BNC plug.**2. General specifications**

- (1) **Product name** Crimp type 75 Ω BNC right angle plug
 (2) **Model name** BCP-LD25HD
 (3) **Applicable standard** JIS* C 5412 (*Japanese Industrial Standard) / IEC 169 - 8
 (4) **Nominal impedance** 75Ω unbalanced
 (5) **Construction** As shown in the drawing (BL620).
 (6) **Weight** Approx 25 g (Including center contact and crimp sleeve)
 (7) **Packaging** 20 pcs / package (158×132×40 mm)
 (8) **Designation** Stamp brand name on coupling sleeve.
 (9) **Applicable cable** L-2.5CHD
 (10) **Crimp tool** Hand crimp tool: TC-1 / Die: TCD-35CA

3. Ratings

- (1) **Operating temperature** -40 °C ~ +120 °C
 (2) **Operating humidity** ~90 %

4. Characteristics**4.1 Electrical characteristics** As shown in **Table 1****Table 1**

Items	Specified values	Test methods
Insulation resistance	1000Ω or more	Measurement shall be made between the contacts, after an electrification time of 1 min with a d.c. voltage of 500V.
Voltage proof	Without any damage such as electric breakdown etc.	1500 V a.c. shall be applied for 1 min between the contacts. Trip current :0.5mA.
Contact resistance	Between external contacts: 3 mΩ or less Between center contacts: 6 mΩ or less	Measurement shall be made between the contacts, with engaging a plug and a receptacle. (1 kHz:1 mA a.c.)
Return loss	26.4 dB or more (~3 GHz) 20 dB or more (~6 GHz) 10 dB or more (~12 GHz)	An applied cable shall be attached to the plug, then it shall be terminated with 75 Ω. The measurement frequency up to 12 GHz.

4.2 Mechanical characteristics As shown in **Table 2****Table 2**

Items	Specified values	Test methods
Intermatability	To be engaged without any abnormality.	The plug and an applicable receptacle shall be engaged.
Fixing force of contact with lock mechanism	No displacement more than 0.5 mm.	Tensile strength of 19.6 N shall be applied to the axial direction.
Strength of coupling mechanism	Coupling sleeve shall not be disconnected or no deformation shall be made.	The plug and a receptacle shall be engaged, after which tensile strength of 245 N and rotation strength of 2.5 N·m shall be applied.
Cable connecting force	200 N or more for L-2.5CHD	An applied cable shall be attached to the plug, after which tensile strength shall be applied.
Mechanical operation (repeated)	Contact resistance: 10 m Ω or less	The endurance test consists of repeated engagement and separation of connector pairs. The measurement shall be made after 5000 cycles.

4.3 Environmental characteristics As shown in **Table 3****Table 3**

Items	Specified values	Test methods
Corrosion resistance (Salt mist)	Appearance: By visual inspection, without noticeable rust. Contact resistance: 50 m Ω or less	The connector shall be subjected continuously to a fine mist of salt solution at a temperature of 35±2 °C for 48 h (Salt solution concentration: 5±1 % by weight). Then it shall be subjected to standard atmospheric conditions. After removing the salt deposits by water, the appearance of the connector shall be checked.

5. Measurement conditions Unless otherwise specified, the standard range of atmospheric conditions for making measurements and tests are as follows: Ambient temperature (15 °C to 35 °C), Relative humidity (25 % to 75 %), Air pressure (86 kPa to 106 kPa). If there is any doubt about the results, measurements shall be made within the following limits: Ambient temperature (20±1 °C), Relative humidity (63 % to 67 %), Air pressure (86 kPa to 106 kPa).