

VL35

3.5" 4K Signal Support HDMI On-Camera Field Monitor

ONE SHEET

Overview

Big things come in small packages. That is definitely the case with the VL35, a compact on-camera field monitor that packs a ton of features including support for 4K resolution. This 3.5" display can handle your 4K and Ultra HD footage and also help you focus with a Pixel-to-Pixel mode. The on-camera monitor's small size makes it ideal for gimbals and lightweight camera systems especially those without a built-in display like the GoPro.



VL35 | 3.5" 4K Signal Support HDMI Field Monitor | **UPC Code:** 847983018086

Special Features

- Resolution of 800 x 480
- 4K & Ultra HD Support via HDMI
- HDMI Input & Output
- Composite Input
- Histogram
- Peaking, False Color, Pixel-to-Pixel & Clip Guides
- Headphone Output

Recommended For

- Field Production



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

VL35

Features you need, Prices you want.

Big 4K Capabilities in a Small Size

The VL35 takes 4K or Ultra HD images and scales them down to the native resolution, producing very sharp images. With the 1:1 Pixel-to-Pixel mode, you can get down to the individual pixels and ensure that everything is in focus, making it valuable for HD footage.

Small & Lightweight

The VL35's small size is extremely useful when filming in tight spaces and where weight savings are important such as with gimbals. Today's ever-shrinking cameras don't always come with built-in screens, making an external monitor like the VL35 necessary.

Inputs & Outputs

The VL35 includes HDMI input and output as well as a composite input via a 3.5mm connector. For audio monitoring, it also features a headphone output. A full-size USB connector comes in handy for future firmware updates.

Software Features

To assist you during your productions, the VL35 has all of our standard software features such as false color and histogram to get the perfect exposure, peaking for focus assist, pixel-to-pixel, frame guides, and much more!

In the Box

The VL35 On-Camera monitor comes with: a shoe mount, a screen cleaning wipe, a USB drive for software updates, and a Canon E6 battery plate.

What's Included

- 1 x AC Adapter
- 1 x AV Break-Out Cable
- 1 x Canon E6 Battery Plate
- 1 x Screen Cleaning Wipe
- 1 x Shoemount
- 1 x USB Drive
- 1 x VL35 Monitor

Optional Accessories

- MA207** 7 In. Articulating Arm
- MA211** 11 In. Articulating Arm
- MA211-R** 11 In. Articulating Arm w/ Single Rod Mount
- BP5-C** Canon 900 Battery Plate
- BP5-E6** Canon LP-E6+ Battery Plate
- BP5-P** Panasonic D54 Battery
- BP5-S** Sony L Series Battery Plate
- BP5-N** Nikon EN-EL15 Battery Plate
- BP5-PG6** Panasonic G6 Battery Plate
- BP5-SU** Sony BP-U Series Battery Plate

Specs

Backlight	LED
Color Depth	16.7 Million
Color System	PAL / NTSC / SECAM (Auto-Detected)
Contrast Ratio	800:1
Diagonal	3.5 In.
Dimensions	4 x 2.9 x 0.7 In.
Inputs	HDMI, Composite
LCD Brightness	315 cd/m2
Material	Heavy Duty Plastic
Operating Volts	DC 6-24V
Outputs	HDMI
Power Consumption	2.5 W
Resolution	800 x 480
Viewing Angle	160 (H) 160 (V)
Weight	0.2 lbs
Shipping Dimensions	3.5 x 7.75 x 6.25 In. 8.8 x 19.6 x 15.8 cm
Shipping Weight	2 lbs / 0.45 kg

Video Signals

HDMI	720x480i & 720x480p @ 59.94, 60 Hz
	720x576i @ 50 Hz
	1280x720p @ 23.97, 24, 25, 29.97, 30, 50, 59.94, 60 Hz
	1920x1080i @ 50, 59.94, 60 Hz
	1920x1080psf @ 24, 25, 29.97, 30 Hz
	1920x1080p @ 23.97, 24, 25, 29.97, 30, 50, 59.94, 60 Hz
	3840x2160p @ 24, 25, 30 Hz
Composite	4096x2160p @ 24 Hz
	NTSC-M, NTSC-J, NTSC 4.43
	PAL B/G H I D, PAL M, PAL N SECAM



ikan

Houston, Texas

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com