

SSPC CABLE SERIES

AC POWER CABLE

Laird AC power cables are built to exceed industry standards. The rugged SSPC Cable series are built to withstand serious abuse from pulls, yanks, forklifts, smashes, bangs, load-ins and load-outs!

Features:

- Standardized, heavy, rubber-jacketed cable for usage in dry, moist, and wet rooms as well as outdoors.
- Resistant to Oil, ozone, weathering effects, greases, water, UV radiation (Sun Res)
- Mine Safety and Health Administration (MSHA)
- Flame-Retardant Acc to CSA FT2
- Device Type: Straight Blade Plug
- Flammability: Rated HB or better UL94
- NEMA: 5-15P

Specifications:

- **Cable**
 - Type: SJOOW
 - Nom Outer Diameter: 11.45mm
 - Outer Jacket: Black Rubber (CPE)
 - Insulation: Rubber (EPR)
 - Number of conductors x AWG: 3x12
 - Min. Bend Radius Flexing: 10x Outer Diameter
 - Min. Bend Radius Static: 6x Outer Diameter
 - Temp. Range Flexing: -4°F to 194°F (-20°C to +90°C)
 - Temp. Range Static: -40°F to 194°F (-40°C to +90°C)
 - Max. Operating Temp of Conductor: 194°F (+90°C)
 - Nominal Voltage: AC U 300 V
 - Test Voltage Conductor: 2500V
 - Carrying Capacity: 25 amps
 - Weight: 0.14lbs/ft (217kg/km)
- **Outlet**
 - Amperage: 15A
 - Voltage: 125 VAC
 - Operating Temp.: -40°F to 140°F (-40°C to 60°C)
- **Plug**
 - Amperage: 15 A
 - Voltage: 125 VAC
 - Environment: Dry

