

LAIRD RTBNC-4694-XXX DATASHEET

The Laird RTBNC-4694 UHD BNC Cable Assembly is specifically designed for high-performance 12G-2K video applications. It features Neutrik rearTWIST UHD BNC connectors and Belden RG6 4694R cable, providing extended bandwidth. The innovative rear twist technology simplifies insertion and removal of connectors, ensuring easy interface with patch bays without the need for special removal tools. The cable's construction includes a solid bare copper conductor, gas-injected foam HDPE insulation, Duobond II + tinned copper braid shield, and a PVC jacket. Belden's certified max transmission distance: 12G Signals up to 257ft, 6G up to 374ft, and 3G up to 538ft. Laird's certified max transmission distance: 190 Feet for 12G/4K.

** Laird certified lengths are defined as max transmission where signal integrity remains 100% functional without any CRC errors, your 12GSDI ST 2082 signals may function at or beyond the manufacturer-certified lengths without issues- however when CRC errors are present there could be drops in audio, video, meta and ancillary data. In most circumstances, video integrity remains intact at OEM distance **

Features:

- Neutrik rearTWIST UHD BNC designed for UHD-data Transmissions
- Fully Compatible with conventional BNC Chassis Connectors
- Improved return loss values at high frequency
- Swiss Antraloy Plating
- Indoor-Riser Rated
- UL1666 compliant and CMR compliant
- Suitable applications: Ultra-High-Definition Digital Video, 4K Single-link 12 Gb/s UHDTV, 4K D-Cinema, 8K Quad-link UHDTV



LAIRD RTBNC-4694-XXX DATASHEET

Specifications:

- **Cable Type:** RG6
- **AWG:** 18
- **Stranding:** Solid
- **Number of Coax:** 1
- **Conductor Material:** SC (Silvered Copper)
- **Conductor Diameter:** 0.040in (1.016mm)
- **Outer Jacket Material:** PVC (Polyvinyl Chloride)
- **Outer Jacket Nom Diameter:** 0.274in (6.96mm)
- **Overall Nom Diameter:** 0.274in (6.96mm)
- **Insulation:** Gas Injected PE-Polyethylene (Foam)
- **Insulation Diameter:** 0.180in (4.57mm)
- **Outer Shield Layer 1:** Tape
- **Outer Shield Layer 1 Material:** Tri-Laminate (Alum+Poly+Alum)100% coverage
- **Outer Shield Layer 2:** Braid
- **Outer Shield Layer 2 Material:** Tinned Copper (TC) 95% coverage
- **Nom Impedance:** 75 Ω
- **Nom Capacitance Conductor to shield:** 15.9 pF/ft (52.2 pF/m)
- **Nom Velocity of Propagation:** 85%
- **Nom Conductor DC resistance:** 6.4 Ohm/1000ft
- **Nom Outer Shield DC resistance:** 2.8 Ohm/1000ft (9.2 Ohm/km)
- **Return Loss:**
 - 5-1600 MHz: 23dB
 - 1600-4500 MHz: 21dB
 - 4500-12000 MHz: 15dB
- **Min Bend Radius:** 2.75in (69.9mm)
- **Min Pulling Tension:** 69lbs (31kg)
- **Max Operating Voltage:** 300 V RMS
- **Operating Temperature:** -22°F to 167°F (-30°C To +75°C)
- **Weight:** 0.04lbs/ft

LAIRD RTBNC-4694-XXX DATASHEET

Specifications:

Neutrik rearTWIST UHD BNC Connector:

- **Connection Type:** BNC
- **Shell:** Brass
- **Shell plating:** Antraloy
- **Insertion Force:** <25 N
- **Lifetime:** >1000 Mating Cycles
- **Contacts:** Brass 0.2 μm AuCo
- **Contact Resistance Inner:** $\leq 3 \text{ m}\Omega$
- **Contact Resistance outer:** $\leq 2 \text{ m}\Omega$
- **Dielectric Strength:** 1.5 kVdc